

Technical Data Sheet

HECK BK FLEX

(Dispersion Adhesive)

HECK BK FLEX:	Dispersion-based flexible adhesive
Properties:	<ul style="list-style-type: none"> – can be applied by hand – highly flexible – high adhesive strength – color: natural white – ready-to-use out of the bucket
Areas of Application:	For exterior and interior use; suitable for wall base application. For bonding EPS (polystyrene) insulation boards in HECK insulation systems on low-absorbent substrates, e. g. woodchip or plaster-fiber boards or similar substrates in ready-built wooden constructions.
Composition:	Polymer dispersion
Technical Data:	Specific weight: 1.49 kg/litre
Coverage:	Approx. 1.5 kg/m ² when using a 2 mm notch; maximum application layer thickness 4 mm
Substrate:	Even, structurally sound, clean, dry, free of grease and dust
Application and Substrate Temperature:	+ 5 °C minimum (during both day and night)
Application:	<p>The data is valid for even, smooth substrates; coverage decreases where unevennesses have to be levelled!</p> <p>Notched trowel application (4 mm notch) on insulation board or substrate; place boards on substrate immediately (danger of skin formation).</p> <p>Curing time (depending on weather):</p> <ul style="list-style-type: none"> – on low-absorbent substrates: tear-off resistant after 4 to 8 hours – on non-absorbent substrates: tear-off resistant after 1 to 2 days
After Treatment:	Protect from frost and rear moisture intrusion.
Notes:	<ul style="list-style-type: none"> – please observe HECK application guideline – clean tools with water immediately after use
Safety Instructions:	<p>Protect eyes and skin against contact with the product. If product gets on skin, wash off with water and soap (under no circumstances use solvents). If product gets in eyes, flush with plenty of water immediately and seek medical attention. Only work in well-ventilated areas; don't smoke, eat or drink during work. If product is swallowed or if symptoms occur, seek medical attention. Wear suitable protective gloves. Keep product out of the reach of children.</p> <p>For further information, refer to Safety Data Sheet.</p>
Storage:	Store in a cool but frost-free place; shelf-life in original container: 12 months maximum. After opening, keep container tightly closed and use up soon.
Quality Control:	Internal and external production process control.



The information given herein is based on our present knowledge and experience. However, it implies no liability on our part. We reserve the right to make changes according to technological progress or further developments. This information serves to describe the properties of our products and services, and no warranty is intended or implied. The customer is not released from the obligation to conduct careful inspection of the functions and applications of incoming goods by qualified personnel. This is also valid with regard to existing third party intellectual property rights. Reference to trade names used by other companies is neither a recommendation nor does it imply that other similar products could not be used. With this publication, earlier Technical Data Sheets become invalid.

HECK Wall Systems GmbH
 Thörlauer Straße 25
 95615 Marktrechwitz / Germany
 T: +49 9231 802-330
 F: +49 9231 802-330
www.wall-systems.com