

Technical Data Sheet

HECK UG

(Universal Primer)

HECK UG:	Solvent-free, pigmented, quartz-filled primer for exterior and interior use
Properties:	Easy to apply, quartz-filled, highly saponification resistant, solvent-free, low-odor. Results in a tactile surface, and is water vapor permeable. Reduces and regulates water absorbency of highly or unevenly absorbent substrates; increases adhesion properties.
Colors:	White, or as per Color Sensation color fan deck; for other colors, please ask.
Areas of Application:	For exterior and interior use. For the priming of structurally sound, absorbent, mineral or organic bonded substrates. Also for smooth plaster or plaster-lime render surfaces and on plasterboard. As primer for mineral and organic bonded HECK finishing coats; also for HECK insulation systems. The responsibility for any usage outside these areas of application lies solely with the user.
Composition:	Polymer dispersion, pigments, fine quartz grit; non film-building.
Coverage:	0.2 - 0.3 l/m ² (coverage may decrease with highly absorbent substrates)
Application and Substrate Temperature:	+ 5 °C minimum; lower temperatures during the curing phase can have a sustained negative effect on product properties.
Substrate:	Make sure the substrate has hardened and is structurally sound, clean, dry, and free of grease. Make sure freshly-applied renders and concrete have sufficiently set. Before priming, make sure all parts not intended for priming are well-covered. Should the product get on unprotected parts, remove it immediately. Stir up content of container thoroughly before usage.
Application:	Apply HECK UG undiluted or diluted with max. 5 % of water once by roller or brush application. Before performing subsequent coatings: allow to dry for at least 5 hours, depending on environmental conditions.
After Treatment:	Protect freshly-applied primer from premature dehydration (sun, wind, high temperatures), frost and rain.
Surface Coating:	with HECK finishing coats: HECK ED, HECK STR, HECK SIP, HECK SHP; HECK Flachverblender (facing slips)
Storage:	Store in a cool place that is free from frost. After opening, keep container tightly closed. Shelf-life in original container: approx. 12 months.



The information given herein is based on our present knowledge and experience. However, it implies no liability on our part. We reserve the right to make changes according to technological progress or further developments. This information serves to describe the properties of our products and services, and no warranty is intended or implied. The customer is not released from the obligation to conduct careful inspection of the functions and applications of incoming goods by qualified personnel. This is also valid with regard to existing third party intellectual property rights. Reference to trade names used by other companies is neither a recommendation nor does it imply that other similar products could not be used. With this publication, earlier Technical Data Sheets become invalid.

HECK Wall Systems GmbH
 Thöläuer Straße 25
 95615 Marktredwitz / Germany
 T: +49 9231 802-330
 F: +49 9231 802-330
www.wall-systems.com